



WOMEN WELFARE HYGIENIC PRODUCTS

AN ISO & CE Certified

MSME CERTIFIED

GEM Registered Supplier



Wisdom For Your Life

Sanitary Napkin Incinerator with Separate Smoke Control Unit

Wall Mountable & Front loading Army Color fully Automatic machine





Burning Capacity: 400 PADS/Day

Burning Capacity:- 380 to 400 Pads per day.
20-25 pads per cycle within 20 to 25 minutes.

** Insert up to 12 pads at a time.

Burning Capacity
380-400
PADS/DAY


20-25
PADS/CYCLE



Dimensions

Incinerator: L-305 mm x B-305 mm x H-525 mm

SCU: L-305 mm x B-305 mm x H-150 mm,



Machine Features & Specification

- 01 Seprate Smoke control unit
- 02 Napkin Drop Point
- 03 Ash Collection Trey
- 04 Indicator
- 05 Start Push Button
- 06 Temp & Burning Time Display
- 07 Smoke exhaust pipe
- 08 MCB Control



Operating Mechanism

Instruction for use:

- 01): Connect the unit with supply through **16 AMP** plug.
- 02): Turn "**ON**" MCB to start the machine.
- 03): Open the door & put the used napkin in drop point
- 04): Close the loading door properly
- 05): Press "**PUSH**" button for burn napkins
- 06): Wait for 20-25 minutes for burning napkin
- 07): Machine will shutdown automatically
(Auto turn off feature)
- 08): Ash collection tray for easy cleaning



Electric Socket
board (16 Amp)

Put Your
Napkin here



Easy Wall Mountable Using Screw

Box Component & Accessories:



More Information



Mode Of Function	Electronically Operated, Fully Automatic
Seprate Smoke Control	Two Activated Carbon Ceramic Blanket Filter For Filtration Of Smoke Emission And Odour Control. (With Exhaust Fan)
Electrical Part	1200W Ceramic Heater, Power Supply 230v With Safety MCB (16Amp), Indicator, Push Button,
Machine Functioning	Burn Used Sanitary Napkins To Sterile Ash And Stop Automatically (Auto Turn Off Feature), Easy Removing Ash Collecting Tray Ensures Cleanliness.
Micro Controller	Provided Automatic Digital Display Controller To See Actual Set Timer And Temperature
Burning Waste	Completely Burn The Solid Napkin, Residue Ash Per Napkin Less Them 1 Milligram
Temperature	Minimum Burning Temperature 400 Degree Inner Burning Chamber And Skin Temperature Of The Unit Under Operation 16°C
Material Of Thermal Insulation	Double Thermal Insulation For Extra Protection Of Ceramic Fibre Board (Thickness: 25mm) & Glafibre Blanket (Density 64)
Machine Material	Mild Steel Boby With Epoxy Anti Rust Proof Powder Coated For Superior Finish (DFT 100 Micron
Emission Outlet Pipe Location	Top Of Machine (To Be Supplied Along With Machine 2 Mtr.)
Warranty	12 Months Standard Brand Warranty
Type Of Packaging	Packing Of Thermocol And Carton Cardboard Fitment Box
Easy To Installtion	With The Help Of Mounting Accessories Provided , Hang The Machine On Wall & Start Collecting The Napkins.
Customer Support	24x7 Customer Support



*Thanks for
connecting, us...*

Office & Manufacturing Unit: VP INDUSTRIES.

**A0-91, Amrit Steel Compound, South Side Industrial
Area, Ghaziabad-201001**

AN ISO & CE Certified

MSME CERTIFIED

GEM Registered Supplier

 **+91-8512895000**



 **+91-9560532288**

